

List of Tables

Table 1.3.1. Major parameters of the RHIC machine.	6
Table 1.4.1. Specifications of the superconducting cable for the RHIC arc dipole and quadrupole magnets.	12
Table 1.4.2. Measured normal harmonics in the RHIC arc dipole mag- nets	20
Table 1.4.3. Measured skew harmonics in the RHIC arc dipole mag- nets	21
Table 3.1.1. The B-H table used in the POISSON calculations.	95
Table 3.2.1. Computed transfer function as a function of the yoke in- ner radius in the RHIC arc dipole magnet.	108
Table 3.2.2. Computed saturation induced allowed harmonics as a function of the yoke inner radius in the RHIC arc dipole magnet.	108
Table 3.2.3. The computed change in transfer function, b_2 and b_4 as a function of the yoke outer radius in the SSC dipole magnet.	111
Table 3.2.4. Computed fringe field at 6500 A in the SSC dipole mag- net.	113
Table 3.2.5. The saturation induced harmonics as a function of the bypass hole angular location in the RHIC arc dipole.	118
Table 3.2.6. The saturation induced harmonics as a function of the bypass hole location in the RHIC D0 dipole.	122
Table 3.2.7. The saturation induced harmonics as a function of various parameters of the saturation suppressor hole.	125
Table 3.2.8. The saturation induced harmonics in the SSC dipoles when the yoke alignment keys are made of stainless steel.	131
Table 3.2.9. The saturation induced harmonics in the RHIC arc dipoles when the yoke alignment keys are made of iron.	131
Table 3.2.10. The saturation induced harmonics in the RHIC arc dipoles when the yoke collaring keys are made of stainless steel.	133

Table 3.2.11. The saturation induced harmonics in the RHIC arc dipoles when the yoke collaring keys are made of iron.	133
Table 3.2.12. The saturation induced harmonics with a midplane notch in the RHIC arc dipoles.	138
Table 3.2.13. The saturation induced harmonics with a midplane tooth in the RHIC arc dipoles.	138
Table 3.2.14. The saturation induced harmonics in the proposed elliptical aperture SSC dipole.	148
Table 3.2.15. The saturation induced harmonic as a function of angular position at which the yoke inner radius changes.	150
Table 3.2.16. Current dependence in harmonics with a yoke inner radius of 87 mm.	157
Table 3.2.17. Current dependence in harmonics with a yoke inner radius of 92 mm.	157
Table 3.2.18. Current dependence in harmonics with a yoke inner surface defined by two radii.	158
Table 3.3.1. Measured and computed b_2 and b_4 as a function of current in various designs of RHIC arc dipoles.	166
Table 3.5.1. The a_1 harmonic in several SSC dipoles.	186
Table 4.3.1. Harmonics generated by a 25 μm change in wedge thickness in the SSC dipole.	211
Table 4.3.2. Harmonics generated by a 25 μm change in wedge thickness in the RHIC arc dipole.	211
Table 4.4.1. Computed and measured harmonics due to a change in coil midplane gap in the RHIC arc dipole.	213
Table 4.5.1. Computed and measured harmonics caused by an asymmetric change in coil midplane gap in a RHIC insertion quadrupole.	215
Table 4.6.1. A summary of iterations in RHIC insertion quadrupoles without a change in any wedge.	218

Table 5.2.1.	Harmonics from 1.52 mm thick iron tuning shims.	234
Table 5.2.2.	Harmonics from 3.05 mm thick iron tuning shims.	235
Table 5.2.3.	Harmonics from 4.57 mm thick iron tuning shims.	236
Table 5.2.4.	Harmonics from 6.10 mm thick iron tuning shims.	237
Table 5.2.5.	Maximum change in harmonics from a given thickness of tuning shims.	239
Table 5.2.6.	Current dependence in skew harmonics generated by the tuning shims.	244
Table 5.2.7.	Current dependence in normal harmonics generated by the tuning shims.	245
Table 5.2.8.	Maximum low and high field harmonic correction from the tuning shims.	248
Table 6.2.1.	Cable used in SSC 50 mm dipoles.	267
Table 6.2.2.	Low field harmonics in the SSC dipoles.	270
Table 6.2.3.	Computed current dependence in transfer function and b_2 in the SSC dipoles.	274
Table 6.2.4.	Maximum change in harmonics due to yoke saturation in the SSC dipoles.	275
Table 6.2.5.	POISSON calculations of the BNL built SSC dipole.	276
Table 6.2.6.	Peak field in the coil of the SSC dipole.	278
Table 6.2.7.	Expected quench performance of the SSC dipole.	279
Table 6.2.8.	Allowed harmonics due to 0.05 mm errors in the SSC dipole.	281
Table 6.2.9.	Stored Energy and Inductance in the SSC dipole.	282
Table 6.2.10.	Summary of the SSC dipole coil cross section.	285
Table 6.2.11.	Summary of changes in the SSC dipole due to satura- tion.	285

Table 6.3.1. Summary of the RHIC insertion quadrupole design parameters.	288
Table 6.3.2. Coil design for the RHIC insertion quadrupoles.	289
Table 6.3.3. Computed harmonics in the RHIC insertion quadrupole.	295
Table 6.3.4. Computed harmonics with two RHIC insertion Q1 quadrupoles at minimum separation.	299
Table 6.3.5. Peak field in the RHIC insertion quadrupole.	300

COPIES OF PUBLICATIONS